

PRINCIPALES PERFORACIONES ACERO AL CARBÓN

PERFORACIÓN MM	CALIBRE	DISTANCIA ENTRE CENTROS MM	PERFORACIONES POR PULGADA ²	ÁREA ABIERTA %	PESO KG
0.5	28	1.0	700	22.67%	5.4
0.5	26	1.0	700	22.67%	6.4
0.8	26	1.5	380	25.80%	6.2
1	24	2.0	189	22.67%	8.6
1	22	2.0	189	22.67%	10.7
1.5	22	2.5	110	32.65%	10.2
1.5	20	2.5	110	32.65%	12.3
1.5	18	2.5	110	32.65%	16.3
1.5	16	2.5	110	32.65%	20.4
2	22	3.5	62	29.61%	10.3
2	20	4.0	47	22.67%	13.0
2	18	4.0	47	22.67%	17.2
2	16	4.0	47	22.67%	21.5
2	14	4.0	47	22.67%	26.9
2.5	22	4.0	47	35.43%	9.9
2.5	18	4.0	47	35.43%	16.1
2.5	16	4.0	47	35.43%	20.0
2.5	12	4.5	36	27.99%	36.6
3	26	5.0	30	32.65%	6.0
3	24	5.0	30	32.65%	8.1
3	22	5.0	30	32.65%	10.2
3	20	5.0	30	32.65%	12.3
3	18	5.0	30	32.65%	16.3
3	16	5.0	30	32.65%	20.4
3	14	5.0	30	32.65%	25.4
3	12	5.0	30	32.65%	35.6
4	22	5.2	24	53.66%	8.9
4	20	6.0	20	40.31%	11.8
4	18	6.0	20	40.31%	15.6
4	16	6.0	20	40.31%	19.5
4	14	6.0	20	40.31%	24.3
4	12	6.4	18	35.43%	35.1

* EN CASO DE NO ENCONTRAR SUS REQUERIMIENTOS FAVOR DE CONSULTARNOS.

* LÁMINA ESTÁNDAR 1M X 2M

PRINCIPALES PERFORACIONES ACERO AL CARBÓN

PERFORACIÓN MM	CALIBRE	DISTANCIA ENTRE CENTROS MM	PERFORACIONES POR PULGADA ²	ÁREA ABIERTA %	PESO KG
5	26	7.0	15	46.27%	5.5
5	24	7.0	15	46.27%	7.5
5	22	7.0	15	46.27%	9.4
5	20	7.0	15	46.27%	11.3
5	18	7.0	15	46.27%	15.1
5	16	7.0	15	46.27%	18.8
5	14	7.0	15	46.27%	23.5
5	12	7.0	15	46.27%	32.9
6	22	8.0	12	51.01%	9.1
6	20	8.0	12	51.01%	11.0
6	22	9.0	9	40.31%	9.7
6	18	9.0	9	40.31%	15.6
6	16	9.0	9	40.31%	19.5
7	22	10.0	7	44.44%	9.5
7	18	10.0	7	44.44%	15.2
8	22	10.0	7	58.04%	8.7
8	20	10.0	7	58.04%	10.5
8	18	10.0	7	58.04%	13.9
8	16	10.0	7	58.04%	17.4
9	22	12.0	5	51.01%	9.1
9	20	12.0	5	51.01%	11.1
9	18	12.0	5	51.01%	14.6
10	20	13.0	4	53.66%	10.8
10	14	13.0	4	53.66%	22.4
12	20	16.0	3	51.01%	11.0
12	18	16.0	3	51.01%	14.6
12	16	16.0	3	51.01%	18.2
15	16	20.0	2	51.01%	17.8
15	12	20.0	2	51.01%	31.8

* EN CASO DE NO ENCONTRAR SUS REQUERIMIENTOS FAVOR DE CONSULTARNOS.

* LÁMINA ESTÁNDAR 1M X 2M

LÁMINAS PERFORADAS

PRINCIPALES PERFORACIONES EN ACERO INOXIDABLE TIPO 304 Y 316

DIÁMETRO DEL BARRENO		DISTANCIA ENTRE CENTROS MM	BARRENO POR PULGADA ² PULGADA	ÁREA ABIERTA %	CALIBRE EN INTERVALO											
MM	PULGADAS				11	12	14	16	18	20	22	24	26			
0.5	0.0197	1.09	625	19.08%											A	
0.7	0.0276	1.09	354	37.40%											A	
1.0	0.0394	2.00	206	22.67%						A					A	
1.5	0.0591	3.00	85	22.67%						A						
2.0	0.0787	3.50	62	29.61%					A	A					A	
3.0	0.1181	6.50	24	19.32%				X	X	X	X	X	X	X	X	
3.2	0.1260	5.00	30	37.15%				AX	X	X	X	X	X	X	X	X
4.0	0.1575	7.00	15	29.61%				X	X	X	X	X	X	X	X	
5.0	0.1969	8.00	10	35.43%				X	X	X	X	X	X	X	X	
6.0	0.2362	9.00	8	40.31%				X	X	X	X	X	X	X	X	
6.2	0.2441	11.10	4	28.29%	X	X	X	X	X	X	X	X	X	X	X	
7.0	0.2756	11.10	4	36.07%	X	X	X	X	X	X	X	X	X	X	X	
7.9	0.3110	12.70	4	35.09%	X	X	X	X	X	X	X	X	X	X	X	
9.0	0.3543	12.70	4	45.54%		X	X	X	X	X	X	X	X	X	X	
9.5	0.3740	13.50	4	44.91%	X	X	X	X	X	X	X	X	X	X	X	X
12.0	0.4724	18.00	2	40.31%	X	X	X	X	X	X	X	X	X	X	X	X
12.6	0.4961	18.00	2	44.44%	X	X	X	X	X	X	X	X	X	X	X	X

* EN CASO DE NO ENCONTRAR SUS REQUERIMIENTOS FAVOR DE CONSULTARNOS.

* "A" LÁMINAS ESTÁNDAR 1M X 2M

* "X" LÁMINAS MEDIDAS COMERCIALES 3' X 8', 3' X 10', 4' X 8', 4' X 10'.